

We claim:

1.

A method of forming a web comprising:

discharging stock flow from a headbox onto a wire, the stock flow including water and fibers;

5 transferring a vibrational force to the wire by directly contacting the wire with a vibrating element;

changing at least one of the speed at which the wire is travelling and the frequency of the vibrational force independently of the frequency of the vibrational force and the speed at which the wire is travelling, respectively; and

10 draining at least some of the water from the stock flow to cause the fibers to form a web.

2. The method of claim 1, wherein transferring a vibrational force to the wire includes transferring a vibrational force having a frequency of at least 1,000 Hertz.

3. The method of claim 1, wherein the wire has a cross-machine direction, and wherein changing the frequency of the vibrational force transferred to the wire includes changing the frequency of the vibrational force transferred to a first section of the wire in the cross-machine direction and independently changing the frequency of the vibrational force transferred to a second section of the wire in the cross-machine direction.

4. The method of claim 1, further comprising adjusting an amplitude of the vibrational force transferred to the wire independently of at least one of the frequency of the vibrational force and the speed at which the wire is travelling.

5. The method of claim 1, wherein transferring a vibrational force to the wire includes transferring a vibrational force to an underside of a substantially horizontal wire.

6. The method of claim 1, wherein transferring a vibrational force to the wire includes transferring a vibrational force to the wire during formation of an embryonic web.

7. The method of claim 6, wherein transferring a vibrational force to the wire includes transferring a vibrational force to the wire before the web has a fibrous consistency of approximately 5 percent.

8. The method of claim 1, wherein the vibrating element is a vibrational head coupled to a vibrating device in a papermaking machine, the method further comprising replacing the vibrational head with another vibrational head during operation of the papermaking machine.

5 9. The method of claim 1, wherein the vibrating element is coupled to a frame of a papermaking machine, the method further comprising damping vibrations from the papermaking machine to the vibrating element.

10. The method of claim 1, further comprising lubricating the wire upstream of the vibrating element.

11. The method of claim 1, further comprising monitoring a vibration level of the vibrating element during operation of the papermaking machine.

1. A vibrational device for use with a papermaking machine, the papermaking machine including a wire for receiving stock flow, the vibrational device comprising:

a vibrational device frame;

at least one vibration-inducing mechanism coupled to the vibrational device frame,

5 the at least one vibration-inducing mechanism operable to generate a vibrational force having a frequency that is independent of a speed at which the wire is travelling; and

a vibrational head coupled to the at least one vibration-inducing mechanism and in direct contact with the wire to impart the vibrational force to the wire.

12. The vibrational device of claim 11, wherein the frequency of the vibrational force is adjustable.

13. The vibrational device of claim 11, wherein the vibrational head has a range of vibrational movement and is in direct contact with the wire in only part of the range of vibrational movement.

14. The vibrational device of claim 11, wherein the at least one vibration-inducing mechanism is a pneumatic mechanism operable to generate a vibrational force having a frequency of at least 1,000 Hertz.

15. The vibrational device of claim 11, wherein the at least one vibration-inducing mechanism is an electro-magnetic mechanism operable to generate a vibrational force having a frequency of at least 1,000 Hertz.

20 16. The vibrational device of claim 11, wherein the vibrational device has at least two vibration-inducing mechanisms, at least one of the vibration-inducing mechanisms controllable independently of another of the vibration-inducing mechanisms to vary vibrational forces between different vibrational heads.

25 17. The vibrational device of claim 11, wherein the wire has a cross-machine direction, and wherein a first one of the at least one vibration-inducing mechanism generates a first vibrational force having a first frequency transferred through a corresponding vibrational head to a first section of the wire in the cross-machine direction, and wherein a second one of the at least one vibration-inducing mechanism generates a second vibrational

force having a different second frequency transferred through a corresponding vibrational head to a second section of the wire in the cross-machine direction.

18. The vibrational device of claim 11, wherein the at least one vibration-inducing mechanism generates a vibrational force of approximately 20 to 7000 pounds having an amplitude of to up to approximately 0.120 inches.

19. The vibrational device of claim 11, wherein the vibrational device is positioned beneath the wire.

20. The vibrational device of claim 11, wherein the papermaking machine has a papermaking machine frame and wherein the vibrational device frame is mountable on the papermaking machine frame.

21. The vibrational device of claim 11, wherein the vibrational device frame extends substantially across the wire.

22. The vibrational device of claim 11, wherein the at least one vibration-inducing mechanism and the vibrational head are coupled via a sliding connection enabling removal of the vibrational head from the vibrational device.

23. The vibrational device of claim 22, wherein the sliding connection is one of a dovetail connection and a T-shaped connection.

24. The vibrational device of claim 11, further comprising a vibration isolator coupled to the vibrational head and positioned to absorb vibrations from the papermaking machine.

25. The vibrational device of claim 11, wherein the vibrational head extends substantially across the wire.

26. The vibrational device of claim 11, wherein the vibrational head has a land area positioned at an angle with respect to the wire and through which the vibrational force is transmitted from the vibrational head to the wire.

27. The vibrational device of claim 26, wherein the vibrational head includes an upstream portion which slopes away from the wire at an angle of between 0 to 15 degrees to push water into the wire during movement of the wire.

28. The vibrational device of claim 26, wherein the vibrational head includes a downstream portion which slopes away from the wire at an angle of between 0 to 5 degrees to induce a vacuum between the wire and the downstream portion of the vibrational head.

29. The vibrational device of claim 26, wherein the land area is convex.

2025 RELEASE UNDER E.O. 14176

30. A method of forming a web comprising:
discharging stock flow onto a wire, the stock flow including water and fibers,
the wire having a cross-machine direction;

transferring a first vibrational force to a first section of the wire, the first
5 vibrational force having a first frequency;

transferring a second vibrational force to a second section of the wire disposed
from the first section of the wire in the cross-machine direction, the second vibrational force
having a second frequency that is different from the first frequency; and

draining at least some of the water from the stock flow to cause the fibers to
10 form a web.

31. The method of claim 30, further comprising changing at least one of the first
frequency of the first vibrational force and the second frequency of the second vibrational
force independently of a speed of the wire.

32. The method of claim 30, further comprising changing the first frequency of
15 the first vibrational force independently of the second frequency of the second vibrational
force.

33. The method of claim 30, wherein the first vibrational force has a first
amplitude and the second vibrational force has a second amplitude, the method further
comprising changing the first amplitude of the first vibrational force independently of the
20 second amplitude of the second vibrational force.

34. The method of claim 30, wherein the transferring a first vibrational force and
transferring a second vibrational force includes transferring the first vibrational force and
transferring the second vibrational force to the wire in a wet-end section of a papermaking
machine during formation of an embryonic web.

25 35. The method of claim 30, wherein transferring a first vibrational force includes
transferring vibrational force from a first vibration-inducing mechanism to a vibrational head;
and transferring a second vibrational force includes transferring vibrational force from a
second vibration-inducing mechanism to the vibrational head.

30 36. The method of claim 30, wherein transferring a first vibrational force includes
transferring vibrational force from a first vibration-inducing mechanism to a first vibrational

head in contact with the wire; and transferring a second vibrational force includes transferring vibrational force from a second vibration-inducing mechanism to a second vibrational head in contact with the wire.

37. The method of claim 36, further comprising removing and replacing at least
5 one of the vibrational heads during the discharging, transferring, and draining steps.

38. The method of claim 36, wherein the wire is part of a papermaking machine having a frame, the method further comprising damping vibrations from the first and second vibration-inducing mechanisms to the papermaking machine frame.

39. The method of claim 30, further comprising lubricating the wire with water
10 upstream of the first and second sections of the wire.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
22

40. A vibrational device for use with a papermaking machine, the papermaking machine including a wire for receiving stock flow, the vibrational device comprising:

a vibrational device frame;

a first vibration-inducing mechanism coupled to the vibrational device frame, the first vibration-inducing mechanism operable to generate a first vibrational force having a first frequency;

a second vibration-inducing mechanism coupled to the vibrational device frame, the second vibration-inducing mechanism operable to generate a second vibrational force having a second frequency different from the first frequency; and

a vibrational head coupled to the first vibration-inducing mechanism and to the second vibration-inducing mechanism and directly contacting the wire to impart the first vibrational force and the second vibrational force to the wire.

41. The vibrational device of claim 40, wherein the first frequency and the second frequency are independent of a speed at which the wire travels.

42. The vibrational device of claim 40, wherein the first vibration-inducing mechanism is adjustable to vary the first frequency independently of the second frequency.

43. The vibrational device of claim 40, wherein the first vibration-inducing mechanism and the second vibration-inducing mechanism are pneumatic mechanisms vibrating at a frequency of at least 1,000 Hertz.

44. The vibrational device of claim 40, wherein the first vibration-inducing mechanism and the second vibration-inducing mechanism are electro-magnetic mechanisms vibrating at a frequency of at least 1,000 Hertz.

45. The vibrational device of claim 40, wherein the first vibration-inducing mechanism is controllable independently of the second vibration-inducing mechanism to transfer different forces than the forces transferred by the second vibration-inducing mechanism.

46. The vibrational device of claim 40, wherein the vibration-inducing mechanisms generate vibrational head vibrations having an amplitude of up to approximately 0.120 inches.

47. The vibrational device of claim 40, wherein the vibrational head is positioned perpendicular to a direction of travel of the wire.

48. The vibrational device of claim 40, wherein the papermaking machine includes a papermaking machine frame; and the vibrational device frame includes a truss
5 coupled to the papermaking machine frame and supporting the first vibration-inducing mechanism, the second vibration-inducing mechanism and the vibrational head.

49. The vibrational device of claim 40, wherein the vibrational head is removably coupled to the first and second vibration-inducing mechanisms by a sliding connection.

50. The vibrational device of claim 49, wherein the sliding connection has one of
10 a dovetail profile and a T-shaped profile.

51. The vibrational device of claim 40, further comprising vibration isolators coupled to the vibrational head and positioned to dampen vibrations transmitted from the first and second vibration-inducing mechanisms to the papermaking machine.

52. The vibrational device of claim 40, wherein the vibrational head extends
15 substantially across the wire.

53. The vibrational device of claim 40, wherein the vibrational head has a land area positioned at an angle with respect to the wire and through which the first and second vibrational forces are transmitted from the vibrational head to the wire.

54. The vibrational device of claim 40, wherein the vibrational head includes an
20 upstream portion which slopes away from the wire at an angle of between 0 to 15 degrees to push water into the wire during movement of the wire.

55. The vibrational device of claim 40, wherein the vibrational head includes a downstream portion which slopes away from the wire at an angle of between 0 to 5 degrees to induce a vacuum between the wire and the downstream portion of the vibrational head.

56. The vibrational device of claim 53, wherein the land area is convex.
25

57. A method of drying a web, comprising:
moving the web to a press felt;
pressing the web against the press felt to remove water from the web;
transferring a vibrational force to the press felt by directly contacting the

5 press felt with a vibrating element;

loosening foreign matter in the press felt with the vibrational force from the
vibrating element;

removing loosened foreign matter from the press felt; and
drying the web.

10 58. The method of claim 57, further comprising changing at least one of a speed at
which the press felt is travelling and a frequency of the vibrational force independently of the
frequency of the vibrational force and the speed at which the press felt is travelling,
respectively.

15 59. The method of claim 58, wherein the press felt has a cross-machine direction,
and wherein changing the frequency of the vibrational force includes changing a frequency of
vibrational force transferred to a first section of the press felt in the cross-machine direction
and independently changing a frequency of vibrational force transferred to a second section
of the press felt in the cross-machine direction.

20 60. The method of claim 58, further comprising changing an amplitude of the
vibrational force transferred to the press felt independently of at least one of a frequency of
the vibrational force and a speed at which the press felt is travelling.

25 61. The method of claim 58, wherein transferring the vibrational force to the press
felt includes transferring a first vibrational force with a first vibration-inducing mechanism to
a first section of the press felt and transferring a second vibrational force with a second
vibration-inducing mechanism to a second section of the press felt disposed a lateral distance
from the first vibration-inducing mechanism.

62. The method of claim 61, wherein the first vibration-inducing mechanism is
controllable independently of the second vibration-inducing mechanism.

63. The method of claim 61, wherein transferring a first vibrational force includes transferring the first vibrational force to a vibrational head coupled to the first vibration-inducing mechanism.

64. The method of claim 63, wherein the vibrational head is also coupled to the second vibration-inducing mechanism; and transferring a second vibrational force includes transferring the second vibrational force to the vibrational head.

65. The method of claim 63, wherein transferring the second vibrational force includes transferring the second vibrational force to another vibrational head coupled to the second vibration-inducing mechanism.

66. The method of claim 61, wherein the first and second vibration-inducing mechanisms generate vibration at first and second frequencies, the method further comprising independently varying the first frequency by adjusting the first vibration-inducing mechanism.

67. The method of claim 63, further comprising: removing and replacing the vibrational head with another vibrational head during at least one of the moving, pressing, transferring, loosening, removing, and drying steps.

68. The method of claim 58, wherein the press felt is part of a papermaking machine press section having a frame, the method further comprising at least partially isolating the frame from the vibrational force.

69. The method of claim 58, further comprising lubricating the press felt with water upstream of a location where the vibrational force is transferred to the press felt.

70. A papermaking machine, comprising:
a press positioned to receive a web and to mechanically press the web to
remove water from the web;
a press felt positioned to receive water pressed from the web;
5 a vibrational device located adjacent to the press felt and operable to contact
and vibrate the press felt; and
a dryer positioned to receive the web from the press and to remove water from
the web.

71. The papermaking machine of claim 70, further comprising a lubrication
10 shower positioned upstream with respect to the vibrational device.

72. The papermaking machine of claim 70, wherein the vibrational device is
adjustable to change a frequency of vibrational force transferred to the felt.

73. The papermaking machine of claim 72, wherein the vibrational device is
adjustable independently of a speed of the press felt.

74. The papermaking machine of claim 70, wherein the vibrational device has at
least two vibration-inducing mechanisms, at least one of the vibration-inducing mechanisms
controllable independently of another of the vibration-inducing mechanisms to vary
vibrational forces transferred to different areas of the press felt.

75. The papermaking machine of claim 70, wherein: the press felt has a cross-
20 machine direction; the vibrational device has a least two vibration-inducing mechanisms; a
first one of the vibration-inducing mechanisms is operable to generate a first vibrational force
having a first frequency transferred to the press felt; and a second one of the vibration-
inducing mechanisms disposed in a cross-machine direction of the press felt from the first
vibration-inducing mechanism is operable to generate a second vibrational force having a
25 second frequency transferred to the press felt.

76. The papermaking machine of claim 75, wherein the first vibration-inducing
mechanism is adjustable to change the first vibration frequency independently of the second
vibration-inducing mechanism.

77. The papermaking machine of claim 75, wherein the first vibration-inducing mechanism is adjustable to change an amplitude of the first vibrational force independently of the second vibration-inducing mechanism.

78. The papermaking machine of claim 75, wherein the first and second vibration-inducing mechanisms have respective vibration heads in contact with the press felt and disposed from one another in the cross-machine direction of the press felt.

79. The papermaking machine of claim 75, wherein the first and second vibration-inducing mechanisms are coupled to a vibration head in contact with the press felt.

80. The papermaking machine of claim 70, wherein the vibrational device has a frame mounted to a frame of the papermaking machine.

81. The papermaking machine of claim 70, wherein the vibrational device is operable to vibrate at a frequency of at least 1,000 Hertz.

82. The papermaking machine of claim 70, wherein the vibrational device includes at least one vibration-inducing mechanism and a vibrational head coupled to the vibration-inducing mechanism and in contact with the press felt.

83. The papermaking machine of claim 82, wherein at least one of the vibration-inducing mechanisms is coupled to the vibrational head via a sliding connection.

84. The papermaking machine of claim 70, wherein the vibrational head extends substantially across the press felt.

85. The papermaking machine of claim 82, wherein the vibrational head has a land area positioned at an angle with respect to the press felt and through which vibrational forces are transmitted from the vibrational head to the press felt.

86. The papermaking machine of claim 82, wherein the vibrational head includes an upstream portion which slopes away from the press felt at an angle of between 0 to 15 degrees to push water into the press felt during movement of the press felt.

87. The papermaking machine of claim 82, wherein the vibrational head includes a downstream portion which slopes away from the press felt at an angle of between 0 to 5

degrees to induce a vacuum between the press felt and the downstream portion of the vibrational head.

88. The papermaking machine of claim 85, wherein the land area is convex.

88. The papermaking machine of claim 85, wherein the land area is convex.

89. A method of changing performance of a forming section of a papermaking machine having a wire, the method comprising:

providing a vibrational device having a vibrational device frame coupled to the papermaking machine, a vibration-inducing mechanism coupled to the vibrational device frame, and a vibrational head coupled to the vibration-inducing mechanism;

sliding a first vibrational head with respect to the wire and the vibration-inducing mechanism to disconnect the first vibrational head from the vibration-inducing mechanism;

removing the first vibrational head from the vibration-inducing mechanism;

sliding a second vibrational head with respect to the vibration-inducing mechanism to connect the second vibrational head with the vibration-inducing mechanism; and

positioning the second vibrational head in contact with the wire.

90. The method of claim 89, wherein at least one of the sliding steps is performed while the papermaking machine is in operation.

91. The method of claim 89, wherein sliding the first vibrational head includes sliding the first vibrational head between the vibration-inducing mechanism and the wire.

92. The method of claim 89, wherein sliding the second vibrational head includes sliding the second vibrational head between the vibration-inducing mechanism and the wire.

93. The method of claim 89, wherein sliding the second vibrational head includes sliding the second vibrational head onto the vibration-inducing mechanism via a dovetail joint.

94. The method of claim 89, wherein sliding the second vibrational head includes sliding the second vibrational head onto the vibration-inducing mechanism via a T-shaped joint.

95. A vibrational device for use with a papermaking machine, the papermaking machine including a wire for receiving stock flow, the vibrational device comprising:

a vibrational device frame;

a vibration-inducing mechanism coupled to the vibrational device frame; and

5 a vibrational head coupled to the vibration-inducing mechanism and positioned to directly contact the wire, the vibrational head operable to impart vibrational force to the wire, the vibrational head being removably coupled to the vibration-inducing mechanism via a sliding connection

96. The vibrational device of claim 95, wherein the vibrational head is disconnectable and removable from the vibration-inducing mechanism during operation of the papermaking machine.

97. The vibrational device of claim 95, wherein the sliding connection is a dovetail connection

98. The vibrational device of claim 95, wherein the sliding connection has a T-shaped cross-section.

99. The vibrational device of claim 95, wherein the vibrational head has a land area positioned at an angle with respect to the wire and through which vibrational forces are transmitted from the vibrational head to the wire.

100. The vibrational device of claim 95, wherein the vibrational head includes an upstream portion which slopes away from the wire at an angle of between 0 to 15 degrees.

101. The vibrational device of claim 95, wherein the vibrational head includes a downstream portion which slopes away from the wire at an angle of between 0 to 5 degrees.

102. The vibrational device of claim 98, wherein the land area is convex.

103. The vibrational device of claim 95, wherein the vibrational head has a length substantially the same as a width of the wire.

104. The vibrational device of claim 95, wherein the vibration-inducing mechanism is operable to generate a vibrational force having a frequency of at least 1,000 Hertz.

105. The vibrational device of claim 95, wherein the vibration-inducing mechanism is a first vibration-inducing mechanism, the vibrational device further comprising at least one additional vibration-inducing mechanism, the vibrational head being removably coupled to the at least one additional vibration-inducing mechanism via a sliding connection.

5 106. The vibrational device of claim 105, wherein the first vibration-inducing mechanism and the at least one additional vibration-inducing mechanism are disposed along a cross-machine direction of the wire.

50

107. A vibrational device for use with a papermaking machine, the papermaking machine including a wire for receiving stock flow, the vibrational device comprising:

a vibrational device frame;

at least one vibration-inducing mechanism coupled to the vibrational device

5 frame; and

a vibrational head coupled to the at least one vibration-inducing mechanism and in direct contact with the wire to impart the vibrational force to the wire, the vibrational head including at least one of an upstream portion which slopes away from the wire and a downstream portion which slopes away from the wire.

10 108. The vibrational head of claim 107, wherein the upstream portion slopes away from the wire at an angle of between approximately 0 to 15 degrees.

109. The vibrational head of claim 107, wherein the downstream portion slopes away from the wire at an angle of between approximately 0 to 5 degrees.

110. The vibrational device of claim 107, wherein the at least one vibration-inducing mechanism and the vibrational head are coupled via a sliding connection enabling removal of the vibrational head from the vibrational device.

111. The vibrational device of claim 110, wherein the sliding connection is one of a dovetail connection and a T-shaped connection.

112. A method of forming a web comprising:
discharging stock flow from a headbox onto a wire, the stock flow including
water and fibers;
transferring a vibrational force to the wire by directly contacting the wire with
a vibrating element;
pushing water into the wire with a sloped upstream portion of the vibrating
element;
inducing a vacuum between the wire and the vibrating element with a
downstream portion of the vibrating element; and
draining at least some of the water from the stock flow to cause the fibers to
form a web.

113. The method of claim 112, wherein transferring a vibrational force to the wire
includes transferring a vibrational force to an underside of a substantially horizontal wire.

114. The method of claim 112, wherein the vibrating element is a vibrational head
coupled to a vibrating device in a papermaking machine, the method further comprising
replacing the vibrational head with another vibrational head during operation of the
papermaking machine.